Specifications

-								
1	I	m		n	C	ı٨	n	c
-	I		c		э	ιu		3

Scanning Face		Simplex / Duplex			
Scanning Method		1 line Colour CIS (300 dpi/600 dpi), Black or White Background			
Scanning Resolution	on*1	100 – 600 dpi (1 dpi step) and 1,200 dpi (interpolated)			
		Optical: 300 dpi / 600 dpi (Automatic switch)			
Scanning Speed*2	Binary/Colour	KV-N1058X Simplex: Up to 65 ppm, Duplex: Up to 130 ipm			
A4/Portrait, 200/300 dpi		KV-N1028X Simplex: Up to 45 ppm, Duplex: Up to 90 ipm			
Output Methods		Scan to Email, Scan to FTP, Scan to Shared Folder, Scan to Cloud*3, Scan to SharePoint*3, Scan to PC*4			
Double-Feed Dete	ction	Ultrasonic (The length of documents that can be detected is 70 mm (2.8 in.) or more.)			
Image Compressio	n	MH, MMR , JPEG, JPEG2000			
Binary Mode Halfte	one	Dither, Error Diffusion			
Image Control		Auto Preview, Auto Rescan, Automatic Brightness Adjustment,			
		Multi Colour Drop Out, Dynamic Threshold, White Level From Paper,			
		Image Emphasis Gamma, Automatic Separation, Noise Reduction			
Other Functions		Length Control, Barcode Detection,			
		Patchcode Detection (Type 2, 3, T),			
		Control Sheet Detection, Long Paper, Double Feed Skip			
Documents	Width	48 mm - 216 mm (1.9 in 8.5 in.)			
	Length	Automatic feeding: 54 mm - 356 mm (2.1 in. – 14 in.)			
	, in the second s	Manual feeding: 54 mm - unlimited (2.1 in. – unlimited)*5			
	Thickness	Paper 0.04 mm- 0.5 mm (1.6 mils 19.7 mils.)			
		Passport*6 4.0 mm (157.5 mils.) (including carrier sheet)			
		Note: 1 mil = 0.001 in.			
	Weight	20 g/m² - 413 g/m² (5 lb 110 lb.)			
Card	Format	ISO format			
	Size	85.6 mm × 54 mm (3.4 in. × 2.1 in.)			
	Thickness	0.76 mm (0.03 in.), Embossed card up to 1.4 mm (55.1 mils.)			
Feed Tray Capacity	1	100 sheets: 80 g/m² (21 lb.) High-quality woodfree paper*7			
Supported Operati		Windows Vista® SP2 (32 bit/64 bit), Windows® 7 (32 bit/64 bit),			
	5.5	Windows® 8 (32 bit/64 bit), Windows® 8.1 (32 bit/64 bit), Windows® 10 (32 bit/64 bit),			
		Windows Server® 2003 SP2 (32 bit/64 bit), Windows Server® 2003 R2 SP2 (32 bit/64 bit)			
		Windows Server® 2008 SP2 (32 bit/64 bit), Windows Server® 2008 R2 SP1 (64 bit),			
		Windows Server® 2012 (64 bit), Windows Server® 2016 (64 bit)			
Recommended We	b Browser	Internet Explorer 11, Mozilla Firefox (latest version),			
Recommended web browser		Google Chrome (latest version)			
Interface		USB 3.1 Gen1 (backward compatible)			
		LAN (10Base-T / 100Base-TX / 1000Base-T) *8			
		Wireless LAN (IEEE802.11n/g/b)			
Wireless LAN	Communication standard	IEEE802.11n/q/b			
	Frequency range*9	KV-N1058X U / ML : 2.412 GHz – 2.472 GHz (1 – 13ch)			
	(center frequency) /	KV-N1058X M / B : 2.412 GHz – 2.462 GHz (1 – 11ch)			
	Channel	KV-N1028X M : 2.412 GHz – 2.462 GHz (1 – 11ch)			
External Dimensio	ns	300 mm x 272 mm x 238 mm (11.8 in. x 10.7 in. x 9.4 in.)			
(W X D X H)		(When the exit tray is closed)			
Weight		4.1 kg (9.0 lb.)			
Power Requiremer	nt*10	AC 100 – 127 V, 50/60 Hz, 0.8 A			
		AC 220 – 240 V, 50/60 Hz, 0.4 A			
Power	Maximum (Scanning)	36 W or less			
Consumption	Minimum (Ready)	10 W or less			
	Sleep	2 W or less (USB connection)			
	5.000	2 W or less (Wired LAN Connection)*11			
		2 W or less (Wireless LAN Connection)			
	Power off	AC 100 V - 127 V: 0.3 W or less			
	. ower on	AC 100 V = 127 V: 0.5 W of less AC 220 V = 240 V: 0.5 W or less			
Operating Environment		Temperature: 5 °C - 35 °C (41 °F - 95 °F)			
		Humidity: 20 % – 80 % RH			
Storage Environme	ent	Temperature: -10 °C - 50 °C (14 °F - 122 °F)			
storage environme		Humidity: 8 % – 75 % RH			
Accessories		CD-ROM: Device Driver, ISIS driver software, TWAIN driver software, User utility,			
Accessories					
		Scan Button Setting Tool ^{*12} , Image Capture Plus, Operating Manual, Control sheet			
		Quick Installation Guide, Power cord, USB cable (1.5 m (59 in.) / USB 3.1),			
		Mixed batch card guide, Anti glare film (for **-M model)			
0.11		Flatbed Scanner: KV-SS081*13, Roller exchange kit: KV-SS061,			
Options		Roller cleaning paper: KV-SS03, Carrier Sheet: KV-SS077,			
		Image Capture Plus add-in (single license package): KV-SS092*14,			
		Image Capture Plus add-in (10 license package): KV-SS093*15,			
		1 January Octobergy Diversity of the state o			

mage Capture Plus OCR module for network scan 10-user license package: KV-SS094*16

Kofax

VRS









Panasonic

1.800.635.3587 panasonic.com



*1 When scanning a document larger than A5 size at resolutions over 600 dpi, the scanning may fail due to insufficient memory.

- *2 The scanning speed is the maximum speed of the scanner hardware. It does not include software processing time, data transfer time, etc. The scanning speed measurement is based on Panasonic's measuring method. In case of using this unit with a LAN connection, the scanning speed may be slower due to network traffic. *3 Scan server must be set up. Also, it is necessary to install
- Image Capture Plus into the PC used as a scan server *4 It is necessary to install Image Capture Plus
- nto the target PC. *5 Using "Long Paper", you can scan a long document to
- a series of split scanned images.
 *6 Use the carrier sheet (KV-SS077) to scan passport. Depending on the condition (operating environment, dirt, scratches, etc.) of the carrier sheet or passport, the image processing function may not work properly. Scan beforehand to confirm the scanned image.
- *7 Paper less than 100 mm (3.9 in.) long or legal size paper: 75 sheets
- *8 To assure continued emission limit compliance use only shielded LAN cable. The cable should be a CAT 5 (Category 5) or higher for 10Base-T / 100Base-TX, or CAT 5e (Enhanced Category 5) or higher for 1000Base-T.
- *9 Values differ depending on the country.*10 The power requirement differs depending
- on the country/area. *11 If connected to a network device (hub, router, etc.) that
- supports IEEE802.3az. *12 This tool is used when the scanner is connected via USB
- *13 USB Scanning only. *14 Required to installing OCREngine for Image Capture Plus on
- 2 or more PCs. (For 1 license)
- *15 Required to installing OCREngine for Image Capture Plus on 2 or more PCs.
- (For 10 licenses) *16 To install the scan server, you need this option.

Trademarks and registered trademarks

- ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. ISIS is a registered trademark or trademark of EMC Corporation in the United States and other countries Windows, Windows Vista, Windows Server and Internet Explore are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. - Mozilla and Firefox are registered trademarks of the Mozilla Foundation. - Google and Google Chrome are either trademarks or registered trademarks of Google LLC. All other brand or product names are the property of their respective holders

This product is designed to reduce hazardous chemical substances in accordance with the RoHS directive

These products may be subject to export control regulations.

Panasonic

Securely Share Scanned Data with Easy-to-Use Network Scanner



Large Colour Touch Screen

Flexible Network Connectivity

Advanced Network Security

Document Scanner KV-N1058X KV-N1028X

8-1

Large Colour Touch Screen

Easy-to-use 5-inch Colour Touch Panel Provides Intuitive Operation

With the addition of the mounted 5-inch colour touch screen on the scanner, users can adjust the settings from the touch panel and have quick and easy access to the most used scanning operations. By selecting the desired operation from the menu, users can easily send scanned images or data via various destinations such as email.



Flexible Network Connectivity

Shareable Network Scanners Without PC Give Savings on Total Cost

The variable network connectivity of KV-N1058X/KV-N1028X allows you to connect the scanner to your PC or mobile device over wired or wireless connection according to your business needs. The need for large installation space, and the cost for more PC's are eliminated. This means it also saves you operation cost.

* You must set up a PC as a scan server to scan to Cloud or SharePoint



Advanced Network Security

Advanced Security Features Yield Higher Security Level

Send your scanned data safely and securely with the advanced network security features. The KV-N1058X and the KV-N1028X come with encryption technology that supports SFTP and SSL communication. They also feature User Authentication and Access Control to provide a high level of security to multiple users.





[SSL/TLS and SFTP] communication and SFTP for server communication

Even Faster with Excellent Features

Send Scanned Data via Smartphone

Various Scanning Choices

KV-N1058X/KV-N1028X. No more problems when scanning long paper, passports, bankbooks, or even embossed cards at once.



